
# WEATHERPROOF EMERGENCY REMOTE | NEMA 4X | SANITATION RATED (NSF)





**EA SERIES** 




The FLEA series of NEMA 4 and 4X weatherproof remotes are constructed from durable polycarbonate and are designed to perform in harsh environments. The base is constructed of impact and corrosive resistant Valox® for maximum durability. A plated steel bracket attaches the reflector to the base plate using a threaded nipple and lock nut for tool-less lamp adjustability and ease of relamping. The base plate and polycarbonate cover join together to form a complete assembly that is fully gasketed. The FLEA series is designed with several surface conduit knockout points for ease of installation. The operating temperature is from -22°F up to 104°F (-30°C up to 40°C).

## SANITATION LISTED (SL)

The FLEA is sanitation listing approved. The Intertek verified splash zone listing is equivalent to the NSF standard 2, meeting the rigorous sanitation, electrical safety and performance standards of food service environments.

## **DIMENSIONS (in, mm.)**



Series	А	В	С
FLEA-S	127mm	127mm	102mm
	5"	5"	4"
FLEA-D	178mm	127mm	102mm
	7"	5"	4"

### **ORDERING INFORMATION**

Series	Head #	Voltage / Wattage	Options
FLEA	S (single head)	See lamp selection	TPS (Tamper proof screws)
	D (double head)		KO (Knockouts on housing)
			LC (less canopy)

### LAMP SELECTION

	6V	12V	24V	120V
Incandescent	5.4W, 7.2W, 9W	9, 12, 18W	9, 18W	N/A
Halogen (H)	12, 20W	12, 20W	12, 20W	N/A
MR16	6, 10W	12, 20, 35, 50W	12, 20, 35, 50W	35W
MR16 LED	5, 7W	2, 5, 7W	5, 7W	N/A