
MAVERICK WP REMOTE

WEATHERPROOF REMOTE | NEMA 4X | SANITATION RATED (NSF)





NEMA 4X DESIGN

The MAVERICK WP REMOTE has been designed to perform in applications where the environment would punish any standard remote. The entire internal cavity of the sign is protected from moisture ingress by an extremely resilient gasket.

SPECIFICATIONS: EXTERNAL

The MAVERICK WP REMOTE is designed to withstand the elements and abuse in applications such as schools, corridors, institutions and apartment complexes. The diecast aluminum body and polycarbonate lens offer protection and superior performance. Tamper resistant screws are standard and ensure the integrity of the battery unit.

SPECIFICATIONS: ELECTRICAL

The MAVERICK WP REMOTE series is available with high output LED, MR16 or GU10 lamps.

SPECIFICATIONS: MECHANICAL


The MAVERICK WP REMOTE is constructed of powder coated die-cast aluminum mounting plate with an impact resistant polycarbonate protective lens. The BOLLA WP remote mounting plate is standard in an attractive powder coated silver grey finish. Other colors are available, including custom color matching.

LAMP SELECTION

Lamp	6V	12V	24V	120V
MR16	6, 10W	10, 12, 20, 35, 50	W10, 12, 25, 50W	N/A
MR16 LED	5, 7W	2, 5, 7W	5, 7W	N/A
GU10	N/A	N/A	N/A	20W



dimensions (in, mm.)



Series	А	В	С
MAV-WP-R	61/4 "	81/4 "	33/4 "
	159mm	210mm	95mm

INSTALLATION

The MAVERICK WP REMOTE series remote is supplied with a universal mounting plate for surface ceiling or wall mount applications. Suitable for indoor, outdoor, damp or wet location applications with NEMA 4X protection. The operating temperature is -40°F to 113°F (-40°C to 45°C).

SANITATION LISTED

The MAVERICK WP REMOTE is sanitation approved. The Intertek verified splash zone listing is certified to the NSF Standard 2, meeting the rigorous sanitation, electrical safety and performance standards of food service environments.

WARRANTY

The MAVERICK WP REMOTE comes with a 3-year factory warranty. Lamps are not covered under the warranty. Deliberate damage, misuse, improper installation effectively cancel the warranty.

ORDERING LOGIC

Series	Lamp No.	Voltage/Wattage	Options
MAV-WP-R	1 (single lamp)	See Lamp Selection	CC (custom colour housing)
	2 (double lamp)		BPG9 ¹ (wireguard)

NOTE 1: Order as a separate line item (BPG9).