

ZEPHYR COMBO



Project:	
Type:	
Catalog #:	



ILLUMINATION

- Long lasting, efficient ultra bright white LED light strip.
- 3.1 watts (24 LEDs x 0.13 watts) per light strip.
- Patent-pending high performance, smooth, chrome plated, metallized reflector with acrylic UV stabilized lens for optical light distribution.
- Long life ultra-bright, energy efficient Red or Green LED EXIT sign illumination

ELECTRICAL

- Dual 120/277 voltage.
- Unique bi-color LED indicator alerts occupant on battery condition (Green-normal, Red-check battery).
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 3.6V Long life, maintenance-free, rechargeable NiCd battery. Internal solid-state transfer switch automatically connects the internal battery to Red/Green LED board and the White LED light strip for minimum 90-minute emergency illumination. Fully automatic solid-state, two rate charger initiates battery
- charging to recharge a discharged battery in 24 hours.

MOUNTING

- Universal K/O pattern on back plate for wall mount.




HOUSING

- Patented specification-grade, low profile thin plastic design is ideal for low level applications.
- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.
- EZ snap-out Chevron directional indicators.

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C – 50°C).
- Certified to CEC under Title 20 regulations.

DIMENSIONS



ORDERING INFORMATION

MODEL	No. of FACES		LETTER COLOR		HOUSING COLOR	
ZEP-C	S	Single Face	RD	Red	WH	White
			GN	Green	BK	Black