

Project:	
Type:	
Catalog #:	

**Description:**

Input Voltage/Frequency : LV:AC100-277V 50/60 Hz
 HV: AC200-480V 50/60 Hz

Installation : Mounting bracket or hanging with suspension chain

Housing : Injection molded, high mechanical resistance, light gray polycarbonate

Diffuser : Injection molded, high mechanical resistance, UV stabilized polycarbonate

Driver (0-10V Dim) : MEANWELL / PHILIPS

LED Brand : SMD2835 LG

CRI : Ra>80

Power Factor : PF>0.95

Beam Angle : 120°

IP Rating : IP66

Warranty : 5 years


Operating Temperature Range : -40°C ~ 40°C

150 lm/W

Certifications : UL 1598 || CSA C22.2 NO. 250.0-08 || CSA C22.2 NO. 250.13-14 (LED) || NSF

Option Available:

- A. Polycarbonate Clips
- B. S/S 304 Clips

**Specification:**

Model No.	DLM-60W	DLM-80W	DLM-100W
Power	60W	80W	100W
Lumen	9,000 lm	12,000 lm	15,000 lm
Clips Q'ty(pcs)	22	22	22
Product Size(mm)	2415*115*105	2415*115*110	2415*115*110
LF (mm)	1530	1530	1530
Innerbox Size(mm)	2425*120*110	2425*120*110	2425*120*110
Carton Size(mm)	2445*248*222	2445*248*222	2445*248*222
Q'ty/CTN(pcs)	2	2	2

Ordering:

MINIMUM ORDER QUANTITY : 10 pcs

Model	Wattage	CCT	Voltage	Clips	Mounting
DLM	60W	S = 3000K	LV = 120-277V	A = Polycarbonate	SM = Surface Mount
	80W	I = 4000K	HV = 200-480V	B = Stainless Steel	CM = Cable Mount
	100W	C = 5000K			

Product Size: