TAA SERIES 300W LED HIGH BAY

PROJECT NAME:	AVAILABLE IN 25-500W CONTACT FACTORY
PROJECT NOTES:	

FEATURES & BENEFITS

- Wattage: 300 Watts
- Input Voltage: 100-277VAC / 200-480VAC
- CCT: 3000K 4000K, 5000K, 5700K
- Beam Angle 60° / 90° / 120°
- IP65 Rated for Wet Locations
- 5 Year Standard Warranty, 10 Year Option
- Die-Cast and Forged Aluminum Housing

Revised 2/17/20

Specifications are typical values and may change without notification

efficiency. illuminated.

300W LED LOW PROFILE HIGH BAY

JAYKAL

SPECIFICATIONS TABLE

WATTAGE	300 Watt	**LUMENS**	39,000lm	**EFFICACY**	130≈140lm/W
INPUT VOLTAGE	120-277VAC / 200-480VAC	**POWER FACTOR**	0.95	**CRI**	>80
INPU FREQUENCY	50/60Hz	**CCT**	3000K, 4000K, 5000K, 5700K	**BEAM ANGLE**	60° / 90° / 120°
THD	<20	**ENVIRONMENT**	IP65 Indoor and Wet Locations		
LIFE (L70)	>75,000 Hours	**CERTIFICATIONS**	DLC, UL	**OPERATIONAL TEMP.**	-30°C - 55°C
HOUSING FINISH	Black / White	**ENVIRONMENT**	IP65 Indoor and Wet Locations		
HOUSING MATERIAL	Cold Forged Aluminum Die-Cast Aluminum	**MOUNTING**	Metal Ring Hanger / U-Bracket		
WEIGHT	16.5 lbs.	**DIMENSIONS**	12.6 X 12.6 X 6 in.		
PROTECTION	IP65	**WARRANTY**	5 Year Standard, 10 Year Option		

ORDERING GUIDE

MODEL	-	WATTAGE	-	VOLTAGE	-	CCT	-	SHADE	-	DIMMING
FME-JLS68103-G2HB		**300** = 300 Watt		**277** = 120-277VAC **480** = 200-480VAC		**30K** = 3000K **40K** = 4000K **50K** = 5000K **57K** = 5700K		**N** = No Shade **PC** = Polycarbonate Shade		**PC** = Photo Cell **M** = Motion Sensor **10** = 1-10V

Not all product variations listed on this page are DLC qualified. Visit www.designlights.org/search to confirm qualification.

Contact Jaykal for additional product approval.

Specifications are typical values and may change without notification

efficiency. illuminated.