

Project:	
Type:	
Catalog #:	



This fully weatherproof T5 or T8 unit is designed for use in areas of wet location. Designed to withstand direct contact with rain this unit is corrosion resistant and waterproof. This unit is ideal in areas such as car washes, store fronts, parking garages, kitchens, and chemical plants. The FGVP unit is capable of being hosed down for easy cleaning.

CONSTRUCTION

Exterior housing is designed for single piece injection molded fiberglass/plastic combination blend. Neoprene gasket and stainless steel pressure locks ensure waterproof seal. Interior gear tray is heavy gauge die formed steel which hinges to allow electrical raceway access while remaining attached to luminaire housing during installation and maintenance.

ELECTRICAL

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp and wet location

MOUNTING

The FGVP is available with a stainless steel external hanging bracket. FGVP Series is watertight and must be drilled and sealed for each surface mounting or chain hanging application.




Mounting Brackets Included

WARRANTY & LISTINGS

- 5-year warranty of all electronics and housing.
- UL Certified for damp and wet location

DIMENSIONS



RF	20									
	80%				70%				50%	
RC	70	50	30	10	70	50	30	10	50	30
0	109	109	109	109	107	107	107	107	101	101
1	98	93	89	84	95	91	86	83	86	83
2	89	80	73	67	86	78	72	66	74	69
3	81	70	62	56	78	68	61	55	65	59
4	74	62	53	47	71	60	52	46	57	51
5	67	54	45	39	65	53	45	38	50	43
6	61	48	39	33	59	47	39	33	45	38
7	56	43	35	29	54	42	34	28	40	33
8	52	39	30	25	50	38	30	24	36	29
9	48	35	27	21	46	34	25	21	32	25
10	44	31	24	19	43	31	23	18	30	23

T8	T5	T5HO	Length
F17T8	F14T5	F24T5	28"
F32T8	F28T5	F54T5HO	52"
Tandem 4' Tubes			Length
FF32T8	F28T5	F54T5HO	100"
8 ft Tubes			
T8	T8HO	Length	
F96T8	F96T8HO	100"	



INDUSTRIAL LED UNITS

ORDERING INFORMATION

Max weight = 15lbs / 48" 32lbs / 96"

Series	Size	Lumens	Color	Options
FGVP	2 = 2FT 4 = 4FT 8 = 8FT	2FT 3166 (17W) 4350 (24W) 5470 (31W) 6452 (39W)	8FT 3220 (17W) 4480 (24W) 5705 (30W) 6910 (37W) 8640 (48W) 11797 (70W)	3K 35K 4K 5K
		4FT 3220 (17W) 4480 (24W) 5705 (30W) 6910 (37W) 8640 (48W) 11797 (70W)	13820 (74W) 17280 (96W) 23594 (140W)	EMB=====
				REFS = Silver Reflector OCC-E = External Occupancy Sensor OCC-I = Internal Occupancy Sensor BILEVEL = Bi-level system SS = Stainless Steel Latch POLY = Polycarb lens FR = Frosted lens over LED boards

*0-10v low voltage dimming standard per fixture

*Higher and custom lumen packages available upon request

Specifications Subject To Change Without Notice