

Project:	
Type:	
Catalog #:	



SPECIFICATIONS: INTERNAL

The IDABEL is 100% reliable, there are no internal parts to fail. It is a non-toxic, non-radioactive low profile exit solution. The IDABEL is visible at up to 100 feet.

SPECIFICATIONS: EXTERNAL

Construction: ABS plastic with photoluminescent panel. The IDABEL can be used for high and/or low level installations and has a 25 year life expectancy. It is visible at 100 feet during a blackout condition. The IDABEL meets current building codes, NFPA Life Safety Code 101 and OSHA requirements; International Building Code 2009/2018; International Fire Code 2009/2018.

SPECIFICATIONS: ELECTRICAL

CIRCUIT: Since there is no electricity required, the IDABEL is a safer signage solution, which saves on maintenance and energy costs.

INSTALLATION: Before installation it must be determined that there is a minimum of 5 Fc of LED, Fluorescent, metal halide or mercury vapor light on the face(s) of the sign at all times during building occupancy.

WET | EXPLOSION PROOF | LEED POINTS QUALIFIED

SPECIFICATIONS: MECHANICAL

The IDABEL series utilizes photoluminescent technology which absorbs and stores ambient light. It is a non-toxic, and non-radioactive low profile emergency lighting solution. The IDABEL features field adjustable chevrons and is constructed of ABS plastic with photoluminescent panel. The IDABEL is NON-TOXIC and NON-RADIOACTIVE which eliminates disposal fees.

WARRANTY

The IDABEL Series comes with a 10 year factory warranty. Deliberate damage, misuse, improper installation effectively cancel the warranty.



Series	Face No.	Frame Color	Mounting
IDA	1 (single)	RD (red)	UB (universal mounting bracket)
	2 (double)	GN (green)	
		BK (black)	