# WATONGA SERIES

## SELF-LUMINOUS EXIT SIGN



Project:	
Туре:	
Catalog #:	



### SPECIFICATIONS: INTERNAL

The WATONGA is 100% reliable, there are no internal parts to fail. It is a non-toxic, non-radioactive low profile exit solution. The WATONGA is visible at up to 50 feet.

#### SPECIFICATIONS: EXTERNAL

Construction: ABS plastic with photoluminescent panel. The WATONGA can be used for high and/or low level installations and has a 25 year life expectancy. It is visible at 50 feet during a blackout condition. The WATONGA meets current building codes, NFPA Life Safety Code 101 and OSHA requirements; International Building Code 2009/2018; International Fire Code 2009/2018. Universal bracket allows for ceiling and flag mount installation.

#### SPECIFICATIONS: ELECTRICAL

**CIRCUIT:** Since there is no electricity required, the WATONGA is a safer signage solution, which saves on maintenance and energy costs.

**INSTALLATION:** Before installation it must be determined that there is a minimum of 5 Fc of LED, Fluorescent, metal halide or mercury vapor light on the face(s) of the sign at all times during building occupancy.



#### INDOOR | EXPLOSION PROOF | LEED POINTS QUALIFIED

#### SPECIFICATIONS: MECHANICAL

The WATONGA series utilizes photoluminescent technology which absorbs and stores ambient light. It is a non-toxic, and non-radioactive low profile emergency lighting solution. The WATONGA features field adjustable chevrons and is constructed of ABS plastic with photoluminescent panel. The WATONGA is NON-TOXIC and NON-RADIOACTIVE which eliminates disposal fees.

#### WARRANTY

The WATONGA Series comes with a 10 year factory warranty. Deliberate damage, misuse, improper installation effectively cancel the warranty.

8-3/4"	<exit></exit>	3/4" Thick
	15-3/8"	

Series	Face No.	Frame Color	Lettering Outline	Mounting
WAT	1 (single)	RD (red) <sup>1</sup>	GN (green)	UB (universal mounting bracket)
	2 (double)	GN (green) <sup>1</sup>	RD (red)	
		BK (black) <sup>1</sup>		
		WH (white) <sup>2</sup>		

NOTE 1: Lettering outline not available.

NOTE 2: White frame must specify Red or Green letter outline.