

Project:	
Type:	
Catalog # :	

FME Lighting | 877 - 234 - 8460 | info@fmelighting.com



**IP65
IK09**



SPECIFICATIONS



VOLTAGE	AC100-277V (50/60Hz)
WATTAGE	ADJUSTABLE: 100W/120W/150W
COLOR TEMP	2700K-6500K
OPERATING TEMP	-20°C~+45°C(-4°F~+113°F)
HOUSING	Aluminum with baked varnish finish
LENS	Clear
EFFICIENCY (±10%)	140lm/W
POWER FACTOR	>0.95
CRI	≥70
LED LIFESPAN	50,000 hours
DIMMING	1-10V Dimming
PROTECTION	IP65 & IK09, Surge Protection: 6kV/10kV
WARRANTY	5 Year Limited Warranty

KEY FEATURES

- **Mounting:** Suitable for Ceiling mounting, pendant mounting.
 - Stainless steel clips.
- **Indoor or Outdoor Applications:** Ideal for applications in harsh environments: parking garages, mechanical or electronic processing workshops, storage warehouses, steel mills, gas stations, toll booths, waiting rooms, the platforms of railway stations, indoor stadiums and flower cultivating tents, etc.

DIMENSIONS

Unit: inch/mm



Product Dimension	Packing Size	Net Weight	Gross Weight
420x420x67mm 16.5x16.5x2.6inch	470x465x120mm 18.5x18.3x4.7inch	5.5kg 12.1lbs	6.0kg 13.2lbs

ORDERING INFORMATION

ORDERING GUIDE

Series	Wattage	Voltage	CCT	Color	Beam Angle	Dimming
CAG	V = Selectable (100W/120W/150W)	LV = 100-277 VAC	S = 2700K T = 3000K I = 4000K C = 5000K (Standard) K = 6500K	W = White	W = 40° X = 60° Y = 90° Z = 120° (Standard)	ND = None Dimming D = Dimming