

Project:	
Type:	
Catalog # :	

FME Lighting | 877 - 234 - 8460 | info@fmelighting.com



SPECIFICATIONS

ILLUMINATION

- Ultra bright, energy efficient, long life Red or Green LEDs.

ELECTRICAL

- Dual 120/277 voltage.
- Unique bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check battery).
- 4.8V long life, maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Polycarbonate mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

HOUSING

- 5VA flame retardant, UV-stabilized polycarbonate in white, black or gray finish.
- High-impact resistant, UV-stabilized polycarbonate clear lens.
- Corrosion-resistant enclosure with engineering grade silicone gasket.
- Knockouts provided for conduit feed applications.
- EZ snap-out Chevron directional indicators.


CERTIFICATIONS

- Five year warranty on all electronics and housing.
- Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for wet locations (-20°C – 50°C).
- Certified to CEC under Title 20 Regulations.

OPTIONS

- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
- 2C-120V/2C-277V: Dual circuit option on the AC-only unit enables it to be connected to two different power supplies at the same time.
- TP: Tamper-proof hardware helps discourage unauthorized access to the unit.
- Custom: Signs available with requested "special" wording.

DIMENSIONS



ORDERING INFORMATION

ORDERING GUIDE

Series	Battery	No. Of Faces	Letter Color	Housing	Options
CWL	AC = AC-Only EM = Battery Backup (Cold Weather - Standard)	1 = Single Face 2 = Double Face	RD = Red GR = Green	W = White (with white faceplate) B = Black (with black faceplate) G = Gray (with white faceplate)	SDT = Self-Diagnostics ¹ 2C-120 = Dual Circuit with 120V ² 2C-277 = Dual Circuit with 277V ² TP = Tamper-Proof CUSTOM(_**) = Custom Wording**

* Special voltage & SALIDA face plate options available. Contact Factory.

** Replace the _ with what you would like on the sign

¹ - Available only with EM units

² - Available only with AC units

ELECTRICAL INFORMATION

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)	
	120V	277V	120V	277V
CWL-RED/GREEN	2.7	2.7	0.025	0.011
CWL-RED/GREEN/EM/SDT	3.3	3.4	0.030	0.014
CWL-RED/GREEN-2C	2.4	2.4	0.023	0.011