

Project:	
Type:	
Catalog # :	

FME Lighting | 877 - 234 - 8460 | info@fmelighting.com



SPECIFICATIONS

Construction:

Exterior housing is designed for single piece injection molded fiberglass/plastic combination blend. Neoprene gasket and stainless steel pressure locks ensure waterproof seal.

Interior gear tray is heavy gauge die formed steel which hinges to allow electrical raceway access while remaining attached to luminaire housing during installation and maintenance.

Electrical:

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request.

Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp and wet location


Mounting:

Vapor Tight Unit available with an stainless steel external hanging bracket. WBV Series is watertight and must be drilled and sealed for each surface mounting or chain hanging application.

KEY FEATURES


This fully weatherproof LED unit is designed for use in areas of wet location. Designed to withstand direct contact with rain this unit is corrosion resistant and waterproof. This unit is ideal in areas such as car washes, kitchens, & chemical plants. This Vapor tight unit is capable of being hosed down for easy cleaning

Offers 34% more contact between the lens and the gasket. Guardian Seal is a unique combination of our Injection Molded lens features & high performance "poured in place" gasket. This provides the most advanced sealing system available.




DIMENSIONS

Max weight = 20Lbs / 48"



EXTRA INFORMATION

RF	20									
	80%				70%				50%	
RC	70	50	30	10	70	50	30	10	50	30
RW	70	50	30	10	70	50	30	10	50	30
0	109	109	109	109	107	107	107	107	101	101
1	98	93	89	84	95	91	86	83	86	83
2	89	80	73	67	86	78	72	66	74	69
3	81	70	62	56	78	68	61	55	65	59
4	74	62	53	47	71	60	52	46	57	51
5	67	54	45	39	65	53	45	38	50	43
6	61	48	39	33	59	47	39	33	45	38
7	56	43	35	29	54	42	34	28	40	33
8	52	39	30	25	50	38	30	24	36	29
9	48	35	27	21	46	34	25	21	32	25
10	44	31	24	19	43	31	23	18	30	23



ORDERING INFORMATION

ORDERING GUIDE

Series	Size	Wattage 2FT	Wattage 4FT	CCT	Options
WBV	2 = 2FT 4 = 4FT	3166 (17W) 4350 (24W) 5470 (31W) 6452 (39W)	3220 (17W) 4480 (24W) 5705 (30W) 6910 (37W) 9660 (51W) 13440 (72W) 17280 (96W) 18900 (105W) 20730 (111W) 25920 (144W) 35391 (210W)	S = 3K T = 35K I = 4K C = 5K	EMB= emergency ballast OCC-E = External Occupancy Sensor FR = Frosted lens over LED boards OCC-I = Internal Occupancy Sensor SS= Stainless Steel Latch PC = Nonmetallic Latch POLY= Polycarb lens

*0-10v low voltage dimming standard per fixture

*Higher and custom lumen packages available upon request