

STOCK ONLY Hazardous Location/Explosion Proof - USA Inventory

















Inventory Levels as of 1/3/2025

FME LIGHTING | 877-234-8460 | info@fmelighting.com















Series	Pic ture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Solstice Series Area / Low-High Bay Class I, Division I		SOL-5-LV-C-120-7-NPT-TR/PM-5Y-S Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC	50W	116pcs	7000lm (140LM/W)	5000K Ra70	120° (No Lens)	NEMA 4X UL 1598, UL 1598A, UL 8750, UL 844 CSA C22.2 No. 137, CSA C22.2 No. 250.0 Temp. Code: T5,T6	-40°C to + 65°C
Solstice Series Area / Low-High Bay Class I, Division I		SOL-7-LV-C-120-7-NPT-TR/PM-5Y-S Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC	70W	118pcs	9800lm (140LM/W)	5000K Ra70	120° (No Lens)	NEMA 4X UL 1598, UL 1598A, UL 8750, UL 844 CSA C22.2 No. 137, CSA C22.2 No. 250.0 Temp. Code: T5,T6	-40°C to + 65°C -40°C to + 60°C
Rocket Series Flood Light Class I, Division II		ROC-24-LV-C-TYPEV-XP-5Y-S Trunion 2x 3/4" without exposed power cord 100-277VAC	240W	146pcs	36,000lm	5000K Ra70	120° (No Lens)	NEMA 4X UL 1598, UL 1598A, UL 8750, UL 844 CSA C22.2 No. 137, CSA C22.2 No. 250.0 Temp. Code: T5,T6	-40°C to 50°C (-40°F to 122°F)
Nebula Series Low-High Bay Class I, Division II		NEB-10-LV-C-TYPEV-70CRI-NPT-TR/PM-5Y-S Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC	100W	268pcs Dimmable	10125lm	5000K Ra70	120° (No Lens)	NEMA 4X UL 1598, UL 1598A, UL 8750, UL 844, UL924 CSA C22.2 No. 137, CSA C22.2 No. 250.0 CSA C22.2 No. 141 Temp. Code: T5,T6	-40° to +60°C MAX: -40°C to 65°C
Nebula Series Low-High Bay Class I, Division II		NEB-15-LV-C-TYPEV-70CRI-NPT-TR/PM-5Y-S Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC	150W	390pcs Dimmable	20250lm	5000K Ra70	120° (No Lens)	NEMA 4X UL 1598, UL 1598A, UL 8750, UL 844, UL924 CSA C22.2 No. 137, CSA C22.2 No. 250.0 CSA C22.2 No. 141 Temp. Code: T5,T6	-40° to +55° MAX: -40°C to 65°C
Nebula Series Low-High Bay Class I, Division II		NEB-24-LV-C-TYPEV-70CRI-NPT-TR/PM-5Y-S Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC	240W	266pcs Dimmable	32400lm	5000K Ra70	120° (No Lens)	NEMA 4X UL 1598, UL 1598A, UL 8750, UL 844, UL924 CSA C22.2 No. 137, CSA C22.2 No. 250.0 CSA C22.2 No. 141 Temp. Code: T5,T6	-40°C to +45°C MAX: -40°C to 65°C
LIH Series Linear Light Class I, Division II		LIH-5-LV-50-D-DL-B-TM/PM-3/4-S Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC	50W	81pcs Dimmable	8000lm (160LM/W)	5000K Ra70	Diffused Cover	NEMA 4X UL 844, UL:50/E,UL 1598/A, UL 8750, UL924 CSA C22.2 No. 137, CSA C22.2 No. 250.0 CSA C22.2 No. 141, C22.2 No. 94.1, C22.2 No.94.2	-40°C to + 45°C (-40°F to +113°F)
LIH Series Linear Light Class I, Division II		LIH-10-LV-50-D-DL-B-TM/PM-3/4-S Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC	100W	87pcs Dimmable	16000lm (160LM/W)	5000K Ra70	Diffused Cover	NEMA 4X UL 844, UL:50/E,UL 1598/A, UL 8750, UL924 CSA C22.2 No. 137, CSA C22.2 No. 250.0 CSA C22.2 No. 141, C22.2 No. 94.1, C22.2 No.94.2	-40°C to + 40°C (-40°F to +104°F)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-6-B-C-P-ND Glass Lens	60W	Sold Out	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-6-A-C-P-D Glass Lens	60W	Sold Out Dimmable	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-6L-A-C-P-ND Glass Lens	60W	150pcs	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-6L-B-C-P-D Glass Lens	60W	30pcs 200-480V	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)

TERMS:
1) Shipments are from California. Quantities subject to change on daily basis.

Series	Pic ture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-8-A-I-P-ND Glass Lens	80W	40pcs 4000K	8100lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-8-A-C-P-D Glass Lens	80W	65pcs Dimmable	10400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-10-A-C-P-D Glass Lens	100W	260pcs Dimmable	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-10-A-I-P-ND Glass Lens	100W	50pcs 4000K	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-10-B-C-P-D Glass Lens	100W	68pcs DIM 200-480V	13500 lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-15-A-C-P-ND Glass Lens	150W	Sold Out	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-15-A-C-P-D Glass Lens	150W	400pcs Dimmable	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-15-B-C-P-D Glass Lens	150W	47pcs 200-480V	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-20-A-C-P-ND Glass Lens	200W	Sold Out	28000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-20-A-C-P-D Glass Lens	200W	145pcs 4000K	28000lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-20-A-C-P-D Glass Lens	200W	500pcs Dimmable	28000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-25-A-C-P-D Glass Lens	250W	60pcs Dimmable	35,000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-30-A-C-P-D Glass Lens	300W	60pcs Dimmable	42000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-40-A-C-P-D Glass Lens	400W	20pcs 100pcs ETA to BG 1/29 Dimmable	56000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)















TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Pic ture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Moon Series Highbay Class I, Division II		FME-MOO-4-A-I-ND-5Y	40W	5pcs	8100 lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-MOO-6-A-C-P-ND-5Y	60W	Sold Out	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-MOO-6-A-C-P-D-5Y	60W	75pcs Dimmable	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-MOO-6L-A-C-P-D-5Y	60W	Sold Out Dimmable	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-MOO-8-A-C-P-ND-5Y	80W	Sold Out	10800lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-MOO-8-A-I-P-D-5Y	80W	20pcs Dimmable 4000K	10800lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-MOO-8-A-C-P-D-5Y	80W	500pcs Dimmable	10800lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-MOO-10- A-C-P-ND-5Y	100W	Sold Out	14000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-10- A-C-P-D-5Y	100W	160pcs Dimmable	14000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-15-A-C-P-ND-5Y	150W	Sold Out	21000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-15-A-I-P-D-5Y	150W	Sold Out 30pcs ETA to WH 2/10 Dimmable 4000K	21000lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-15-A-C-P-D-5Y	150W	130pcs Dimmable	21000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-15-B-C-P-D-5Y	150W	20pcs Dimmable 200-480V	21000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-20-B-C-P-ND-5Y	200W	Sold Out	28000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)

TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Pic ture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Moon Series Highbay Class I, Division II		FME-MOO-20-A-I-P-ND-5Y	200W	Sold Out 4000K	28000lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-20-A-C-P-D-5Y	200W	90pcs Dimmable	28000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-20-B-C-P-D-5Y	200W	8pcs Dimmable 200-480V	28000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME MOO-25-A-C P-D-5	250W	50pcs Dimmable	33750lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-30-A-C-P-D-5Y	300W	110pcs Dimmable	42000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-40-A-C-P-D-5Y	400W	20pcs Dimmable	56000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Star Series Highbay Class I, Division I		FME-STA-4-42-A-C-R-D-5Y	40W	10pcs 30pcs ETA to WH 1/15 Dimmable	5400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G ClassIII Temp. Code: T4 Other: IP66 IK1	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-6-42-A-IR-ND-5Y	60W	15pcs 40pcs ETA to WH 1/25 4000K	8400lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G ClassIII Temp. Code: T4 Other: IP66 IK1	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-6-42-A-C-R-D-5Y	60W	176pcs Dimmable	8400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G ClassIII Temp. Code: T4 Other: IP66 IK1	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-8-42-A-IR-ND-5Y	80W	88pcs 4000K	11200lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G ClassIII Temp. Code: T4 Other: IP66 IK1	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-8-42-A-C-R-D-5Y	80W	170pcs Dimmable	11200lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G ClassIII Temp. Code: T4 Other: IP66 IK1	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-10-42-A-C-R-ND-5Y	100W	Sold Out	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-10-42-A-IR-ND-5Y	100W	100pcs 4000K	13500lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-10-42-A-C-R-D-5Y	100W	180pcs 200pcs ETA to WH 1/29 Dimmable	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)

TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Pt ture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Star Series Highbay Class I, Division I		FME-STA-15-42-B-I-R-D-5Y	150W	Sold Out Dimmable 200-480V	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-15-42-A-C-R-D-5Y	150W	168pcs 110pcs ETA to WH 1/29 Dimmable	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-15-42-A-I-R-ND-5Y	150W	73pcs 4000K	20250lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-20-42-A-I-R-ND-5Y	200W	43pcs 4000K	27000 lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-20-42-A-I-R-D-5Y	200W	60pcs Dimmable	27000 lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-20-42-B-C-R-D-5Y	200W	Sold Out Dimmable 200-480V	27000 lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-10-42-A-C-R-D-5Y-OPGG <i>with Frosted Globe & Guard</i>	100W	20pcs Dimmable	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-24-42-A-C-R-D-5Y	240W	Sold Out Dimmable	32400 lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-25-42-A-C-R-D-5Y	250W	60pcs 30pcs ETA to WH 1/25 Dimmable	35000lm	5000K	120°	Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Earth Series Flood Light/HighBay Class I, Division I		FME-EAT-G-6-A-C-P-ND-5Y <i>Glass Lens</i>	60W	150pcs	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	104°F to 131°F (-40°C to +55°C)
Earth Series Flood Light/HighBay Class I, Division I		FME-EAT-G-6-A-I-P-ND-5Y <i>Glass Lens</i>	80W	20pcs 4000K	8100lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	104°F to 131°F (-40°C to +55°C)
Earth Series Flood Light/HighBay Class I, Division I		FME-EAT-G-8-A-C-P-D-5Y <i>Glass Lens</i>	80W	140pcs Dimmable	11200lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 131°F (-40°C to +55°C)
Earth Series Flood Light/HighBay Class I, Division I		FME-EAT-G-10-A-C-P-ND-5Y <i>Glass Lens</i>	100W	7pcs	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 131°F (-40°C to +55°C)
Earth Series Flood Light/HighBay Class I, Division I		FME-EAT-G-10-A-C-P-D-5 <i>Glass Lens</i>	100W	30pcs 100pcs ETA to WH 1/20 Dimmable	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 131°F (-40°C to +55°C)















TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Pic ture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Earth Series Flood Light/High Bay Class I, Division I		FME-EAT-G-10-A-I-P-ND-5 Glass Lens	150W	Sold Out 4000K	20250lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 131°F (- 40°C to +55°C)
Earth Series Flood Light/High Bay Class I, Division I		FME-EAT-G-15-A-C-P-D-5Y Glass Lens	150W	25pcs 100pcs ETA 1/20 Dimmable	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 131°F (- 40°C to +55°C)
Earth Series Flood Light/High Bay Class I, Division I		FME-EAT-G-15-B-C-P-ND-5Y Glass Lens	150W	15pcs 200-480V	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 131°F (- 40°C to +55°C)
MRT Series Maritron Flanged Ceiling Surface Mount, Class I, Division II		MRT-B-4-LV1-C-D-CM Includes 1 Meter Chains and Lift rings	40W	10pcs ETA to WH 1/25 20pcs ETA to WH 2/10 Dimmable	5200-7800lm	5000K	120°	Marine:UL 1598,UL844,UL924 UL 844: Class I, DivisionII, GroupA,B,C, D Temp.Code: T4 Other:IP66 IK10	-40°C to 60°C
MRT Series Maritron Flanged Ceiling Surface Mount, Class I, Division II		MRT-C-4-LV1-C-D-CM Includes 1 Meter Chains and Lift rings	40W	43pcs Dimmable	5200lm	5000K	120°	Marine:UL 1598,UL844,UL924 UL 844: Class I, DivisionII, GroupA,B,C, D Temp.Code: T4 Other:IP66 IK10	-40°C to 60°C
Mercury Series Highbay Class I, Division I		FME-MER-10-A-I-R-ND-5Y	100W	42pcs	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Mercury Series Highbay Class I, Division I		FME-MER-15-A-I-R-ND-5Y	150W	8pcs	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Mars Series Jelly Jar Class I, Division I		FME-MAR-2-A-C-ND-5Y-CGG Clear Globe w/ Wire Guard	20W	33pcs	2700lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Mars Series Jelly Jar Class I, Division I		FME-MAR-3-A-C-P-ND-5Y-CGG Clear Globe w/ Wire Guard	30W	Sold Out	4050 lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Mars Series Jelly Jar Class I, Division I		FME-MAR-3-A-C-P-D-5Y-CGG Clear Globe w/ Wire Guard	30W	93pcs 50pcs ETA to WH 2/10 Dimmable	3900lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Mars Series Jelly Jar Class I, Division I		FME-MAR-4-A-I-P-ND-5Y-CGG Clear Globe w/ Wire Guard	40W	Sold Out 40pcs ETA to BG 1/25 60pcs ETA to BG 2/10 4000K	3900lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Mars Series Jelly Jar Class I, Division I		FME-MAR-4-A-C-P-D-5Y-CGG Clear Globe w/ Wire Guard	40W	Sold Out (On Reserve - 125pcs) 150pcs ETA to WH 1/29 Dimmable	3900lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Universe Series Jelly Jar Class I, Division II		FME-UNI-2-A-C-ND-5Y-OPCM-CGG Ceiling Surface Mount Clear Globe with Wire Guard	20W	110pcs	2800lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Universe Series Jelly Jar Class I, Division II		FME-UNI-3-A-C-ND-5Y-OPCM-CGG Ceiling Surface Mount Clear Globe with Wire Guard	30W (27W)	75pcs	4200lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)



TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Pic ture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Universe Series Jelly Jar Class I, Division II		FME-UNI-2-A-C-ND-5Y-P-CGG <i>Pendant Mount Clear Globe with Wire Guard</i>	20W	Sold Out 147pcs ETA to WH 1/15	2800lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK11	-104°F to 140°F (- 40°C to +60°C)
Universe Series Jelly Jar Class I, Division II		FME-UNI-3-A-C-ND-5Y-P-CGG <i>Pendant Mount Clear Globe with Wire Guard</i> 30W is being updated to 27W	30W (27W)	47pcs	4200lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK11	-104°F to 140°F (- 40°C to +60°C)
Universe Series Jelly Jar Class I, Division II		FME-UNI-2-A-C-ND-5Y-OPWA-CGG <i>90 Degree Wall Mount Clear Globe with Wire Guard</i>	20W	105pcs	2800lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Universe Series Jelly Jar Class I, Division II		FME-UNI-3-A-C-ND-5Y-OPWA-CGG <i>90 Degree Wall Mount Clear Globe with Wire Guard</i> 30W is being updated to 27W	30W (27W)	Sold Out 100pcs ETA to BG 1/29	4200lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-2-2-LV-I-P-ND-5Y	20W	20pcs 4000K	5400lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-2-4-LV-C-P-ND-5Y	40W	80pcs	5400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-4-4-LV-C-P-D-5Y	40W	290pcs Dimmable	5400 lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-4-4-LV-I-ND-5Y	40W	25pcs 4000K	8100lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-4-6-LV-I-P-ND-5Y	60W	40pcs 4000K	8100lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-4-6-LV-C-P-D-5Y	60W	30pcs 40pcs ETA to WH 2/10 Dimmable	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-4-8-LV-C-P-D-5Y	80W	70pcs Dimmable	10800lm	5000K	120°	Marine: UL 1598A, UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G, IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-2-G-4-A-I-R-ND-5Y <i>Glass Lens</i>	40W	10pcs 4000K	5400lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D	-104°F to 140°F (- 40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-2-G-4-A-C-R-ND-5Y <i>Glass Lens</i>	40W	24pcs	5400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D	-104°F to 140°F (- 40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-2-G-5-A-C-R-D-5Y <i>Glass Lens</i>	50W	83pcs 200pcs ETA to WH 1/25 Dimmable	7000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D	-104°F to 140°F (- 40°C to +60°C)

TERMS.

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Pt ture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Sun Series Linear Class I, Division I		FME-SUN-4-G-4-A-C-R-ND-5Y Glass Lens	40W	Sold Out	5400lm	5000K	120°	Class II, Division I & II, Group E, F, G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C, D Class I, Division II, Group A, B, C, D Class II, Division I & II, Group E, F, G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-4-A-C-R-D-5Y Glass Lens	40W	120pcs Dimmable	5400lm	5000K	120°	Class II, Division I & II, Group E, F, G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C, D Class I, Division II, Group A, B, C, D Class II, Division I & II, Group E, F, G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-6-A-I-R-D-5Y Glass Lens	60W	55pcs 4000K	8100lm	4000K	120°	Class II, Division I & II, Group E, F, G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C, D Class I, Division II, Group A, B, C, D Class II, Division I & II, Group E, F, G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-6-A-C-R-D-5Y Glass Lens	60W	220pcs Dimmable	8100lm	5000K	120°	Class II, Division I & II, Group E, F, G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C, D Class I, Division II, Group A, B, C, D Class II, Division I & II, Group E, F, G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-8-A-C-R-ND-5Y Glass Lens	80W	Sold Out	10800lm	5000K	120°	Class II, Division I & II, Group E, F, G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C, D Class I, Division II, Group A, B, C, D Class II, Division I & II, Group E, F, G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-8-A-I-R-ND-5Y Glass Lens	80W	100pcs 4000K	10800lm	4000K	120°	Class II, Division I & II, Group E, F, G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C, D Class I, Division II, Group A, B, C, D Class II, Division I & II, Group E, F, G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-8-A-C-R-D-5Y Glass Lens	80W	60pcs Dimmable	10800lm	5000K	120°	Class II, Division I & II, Group E, F, G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C, D Class I, Division II, Group A, B, C, D Class II, Division I & II, Group E, F, G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-10-A-C-R-D-5Y Glass Lens	100W	3pcs 100pcs ETA to LA 1/15 Dimmable	13500lm	5000K	120°	Class II, Division I & II, Group E, F, G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C, D Class I, Division II, Group A, B, C, D Class II, Division I & II, Group E, F, G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 104°F
Meridian Series Vaportight Class I, Division II		FME-MID-24-3-A-C-P-D-SM-5Y 2FT	30W	40pcs Dimmable	4050lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A, B, C, D Class II, Division I & II, Group E, F, G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 113°F (- 40°C to +45°C)
Meridian Series Vaportight Class I, Division II		FME-MID-24-4-A-C-P-D-SM-5Y 2FT	40W	43pcs Dimmable	5400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A, B, C, D Class II, Division I & II, Group E, F, G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 113°F (- 40°C to +45°C)
Meridian Series Vaportight Class I, Division II		FME-MID-48-5-A-I-P-ND-SM-5Y 4FT	50W	160pcs 4000K	6750lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A, B, C, D Class II, Division I & II, Group E, F, G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 113°F (- 40°C to +45°C)
Meridian Series Vaportight Class I, Division II		FME-MID-48-5-A-C-P-D-SM-5Y 4FT	50W	315pcs Dimmable	6750lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A, B, C, D Class II, Division I & II, Group E, F, G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 113°F (- 40°C to +45°C)
Meridian Series Vaportight Class I, Division II		FME-MID-48-6-A-C-P-D-SM-5Y 4FT	60W	295pcs Dimmable	6750lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A, B, C, D Class II, Division I & II, Group E, F, G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 113°F (- 40°C to +45°C)
Meridian-R Series Hazardous location & NSF Rated Class I, Division II		MID-R-24-3-A-1-C-P-D 2FT 304 Stainless steel White NSF	30W	87pcs Dimmable	4050lm	5000K	120°	NSF-Rated Optional Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A, B, C, D Class II, Division I & II, Group E, F, G Class III Temp. Code: T3 Other: IP66 IK10	-40°C to +40°C (T6) -40°C to +60°C (T5)


TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Pic ture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Meridian-R Series Hazardous location & NSF Rated Class I, Division II		MID-R-48-5-A-C-P-D 4FT 304 Stainless steel White NSF	50W	60pcs Dimmable	6750lm	5000K	120°	NSF-Rated Optional Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII Temp.Code: T3 Other:IP66 IK10	-40°C to +40°C (T6) -40°C to +60°C (T5)
XF Linear Light Class I, Division II		XF-2-4-C-D-Z-WM 2FT	40W	8pcs 40pcs ETA to WH 1/10 Dimmable	5600lm	5000K	120°	Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII Temp.Code: T5/T4 Other:IP66 IK10	T5(-40°C to +40°C) T4(-40°C to +55°C)
XF Linear Light Class I, Division II		XF-4-6-C-D-Z-WM 4FT	60W	50pcs Dimmable	8400lm	5000K	120°	Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII Temp.Code: T5/T4 Other:IP66 IK10	T5(-40°C to +40°C) T4(-40°C to +55°C)
XF Linear Light Class I, Division II		XF-4-8-C-D-Z-WM 4FT	80W	190pcs Dimmable	10800lm	5000K	120°	Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII Temp.Code: T5/T4 Other:IP66 IK10	T5(-40°C to +40°C) T4(-40°C to +55°C)
LFL Series, Flood/Area Light Class I, Division II		LFL-1-E-LV1-C-Z-TM	200W	198pcs	2600lm	5000K	120°	Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII	- 104°F to 131°F (-40°C to +55°C)
LFL Series, Flood/Area Light Class I, Division II		LFL-2-D-LV1-C-Z-TM	150W	47pcs	19500lm	5000K	120°	Temp.Code: T4(LFL2),T3(LFL1) Other:IP66 IK10	- 104°F to 131°F (-40°C to +55°C)
LFL Series, Flood/Area Light Class I, Division II		LFL-2-C-LV1-C-Z-TM	100W	66pcs	13500lm	5000K	120°	Temp.Code: T4(LFL2),T3(LFL1) Other:IP66 IK10	- 104°F to 131°F (-40°C to +55°C)
ZTP Series Exit Light Class I, Division I		ZTP-5-RD-LV Double-Faced with Red letters & White Panel	5W	188pcs	650lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
LUMIX-G Series (LGE) Exit Light Class I, Division II		LGE-5-LV-G-WM Green Leds	5W	18pcs	300lm	5000K	120°	Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII Temp.Code: T5/T4 Other:IP66 IK10	Ta= 0°C to + 45°C, when batteryis charged; Ta= -10°C to + 60°C, when battery discharges
XPESC Combo Class I, Division II		EPESC-A-GN-12V-15-GR-SDT SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.	15W	60pcs	/	Green	120°	Meets UL924, UL844, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes. UL 844: Class I DivisionII, GroupA,B,C, D IP66	0°C – 50°C on 12W / 15W and 10°C- 40°C models. Up TO (-20°C – 50°C). WITH CW OPTION
XPESC Combo Class I, Division II		EPESC-A-RD-6V-15-GR	15W	28pcs	/	Red	120°	Meets UL924, UL844, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes. UL 844: Class I DivisionII, GroupA,B,C, D IP66	0°C – 50°C on 12W / 15W and 10°C- 40°C models. Up TO (-20°C – 50°C). WITH CW OPTION
CRUZ SERIES EXIT Class I, Division II		CRU-1-RD-GY-EM	3W	84pcs	/	Red	120°	Meets UL924, UL844, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes. UL 844: Class I, DivisionII, GroupA,B,C,D IP66	0°C – 50°C on 12W / 15W and 10°C - 40°C models. Up TO (-20°C – 50°C). WITH CW OPTION
CRUZ SERIES EXIT Class I, Division II		CRU-1-RD-GY-EM-SDT SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.	3W	115pcs	/	Red	120°	Meets UL924, UL844, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes. UL 844: Class I, DivisionII, GroupA,B,C,D IP66	0°C – 50°C on 12W / 15W and 10°C - 40°C models. Up TO (-20°C – 51°C). WITH CW OPTION
HEL SERIES EMERGENCY Class I, Division II		HEL-12-15-G	15W	47pcs	/	/	120°	Meets UL924, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes. UL 844: Class I, DivisionII, GroupA,B,C, D IP66	0°C – 50°C) . Up TO (-20°C – 50°C). WITH CW OPTION

TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Picture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
HEL SERIES EMERGENCY Class I, Division II		HEL-12-15-G-SDT SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.	15W	60pcs	/	/	120°	Meets UL924, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes. UL 844: Class I, DivisionII, GroupA,B,C, D IP66	0°C – 50°C) . Up TO (-20°C – 50°C). WITH CW OPTION










TERMS:
1) Shipments are from California. Quantities subject to change on daily basis.

FME LIGHTING | 877-234-8460 | info@fmelighting.com

Inventory Levels as of 1/3/2025








Accessories 13 to 23 are compatible with all series with the exception of the LIH, NEB, SOL & ROC

ACCESSORIES

Picture	Model	Stock Available	Description
	SOL-CM	24pcs	Ceiling Mount Bracket for Solstice Series 4x 3/4"NPT Cable Entries, 3 sealed by blanking plugs
	SOL-WM	24pcs	Wall Mount Bracket for Solstice Series 4x 3/4"NPT Cable Entries, 3 sealed by blanking plugs
	NEB-CM	27pcs	Ceiling Mount Bracket for Nebula Series 4x 3/4"NPT Cable Entries, 3 sealed by blanking plugs
	NEB-WM	27pcs	Wall Mount Bracket for Nebula Series 4x 3/4"NPT Cable Entries, 3 sealed by blanking plugs
	ROC-PLM	50pcs	Rocket Series Pole Adaptor
	1- Meter Safety Chain	20pcs	1- Meter Safety Chain
	Slip Fitter	215pcs	Slip Fitter
	OPEB	240pcs	JUNCTION BOX C1,D1
	FME-MID-PM	90sets	Mounting Pole & Clamp for Meridian (MID) Series fixtures

TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Picture	Model	Stock Available	Description
	OPWA25	136pcs	C1, D1 25 DEGREE WALL MOUNT
	OPWA90	250pcs	C1, D1 90 DEGREE WALL MOUNT & JUNCTION Box
	OPPS25	40pcs 180pcs ETA to WH 1/29	25 DEGREE POLE MOUNT
	OPPS90	90pcs 120pcs ETA to WH 1/20	90 DEGREE POLE MOUNT
	OPWA	129pcs	90 DEGREE WALL MOUNT
	NIP-3/4	300pcs	3/4" THREADED CONDUIT NIPPLE
	HOOK-1	113pcs	3/4" HOOK