

STOCK ONLY Hazardous Location/Explosion Proof - USA Inventory


















FME LIGHTING | 877-234-8460 | info@fmelighting.com

Inventory Levels as of Feb 28, 2025

Series	Picture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Solstice Series Area / Low-High Bay Class I, Division I		SOL-5-LV-C-120-7-NPT-TR/PM-5Y-S Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC	50W	82pcs	7000lm (140LM/W)	5000K Ra70	120° (No Lens)	NEMA 4X UL 1598, UL 1598A, UL 8750, UL 844 CSA C22.2 No. 137, CSA C22.2 No. 250.0 Temp. Code: T5,T6	-40°C to +65°C
Solstice Series Area / Low-High Bay Class I, Division I		SOL-7-LV-C-120-7-NPT-TR/PM-5Y-S Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC	70W	91pcs	9800lm (140LM/W)	5000K Ra70	120° (No Lens)	NEMA 4X UL 1598, UL 1598A, UL 8750, UL 844 CSA C22.2 No. 137, CSA C22.2 No. 250.0 Temp. Code: T5,T6	-40°C to +65°C -40°C to +60°C
Rocket Series Flood Light Class I, Division II		ROC-24-LV-C-TYPEV-XP-5Y-S Trunion 2x 3/4" without exposed power cord 100-277VAC	240W	129pcs	36,000lm	5000K Ra70	120° (No Lens)	NEMA 4X UL 1598, UL 1598A, UL 8750, UL 844 CSA C22.2 No. 137, CSA C22.2 No. 250.0 Temp. Code: T5,T6	-40°C to 50°C (-40°F to 122°F)
Nebula Series Low-High Bay Class I, Division II		NEB-10-LV-C-TYPEV-70CRI-NPT-TR/PM-5Y-S Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC	100W	258pcs Dimmable	10125lm	5000K Ra70	120° (No Lens)	NEMA 4X UL 1598, UL 1598A, UL 8750, UL 844, UL924 CSA C22.2 No. 137, CSA C22.2 No. 250.0 CSA C22.2 No. 141 Temp. Code: T5,T6	-40° to +60°C MAX: -40°C to 65°C
Nebula Series Low-High Bay Class I, Division II		NEB-15-LV-C-TYPEV-70CRI-NPT-TR/PM-5Y-S Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC	150W	363pcs Dimmable	20250lm	5000K Ra70	120° (No Lens)	NEMA 4X UL 1598, UL 1598A, UL 8750, UL 844, UL924 CSA C22.2 No. 137, CSA C22.2 No. 250.0 CSA C22.2 No. 141 Temp. Code: T5,T6	-40° to +55° MAX: -40°C to 65°C
Nebula Series Low-High Bay Class I, Division II		NEB-24-LV-C-TYPEV-70CRI-NPT-TR/PM-5Y-S Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC	240W	234pcs Dimmable	32400lm	5000K Ra70	120° (No Lens)	NEMA 4X UL 1598, UL 1598A, UL 8750, UL 844, UL924 CSA C22.2 No. 137, CSA C22.2 No. 250.0 CSA C22.2 No. 141 Temp. Code: T5,T6	-40°C to +45°C MAX: -40°C to 65°C
LH Series Linear Light Class I, Division II		LIH-5-LV-50-D-DL-B-TM/PM-3/4-S Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC	50W	65pcs Dimmable	8000lm (160LM/W)	5000K Ra70	Diffused Cover	NEMA 4X UL 844, UL:50/E,UL 1598/A, UL 8750, UL924 CSA C22.2 No. 137, CSA C22.2 No. 250.0 CSA C22.2 No. 141, C22.2 No. 94.1, C22.2 No.94.2	-40°C to +45°C (-40°F to +113°F)
LH Series Linear Light Class I, Division II		LIH-10-LV-50-D-DL-B-TM/PM-3/4-S Pendant +Trunion 1x 3/4" without exposed power cord 100-277VAC	100W	41pcs Dimmable	16000lm (160LM/W)	5000K Ra70	Diffused Cover	NEMA 4X UL 844, UL:50/E,UL 1598/A, UL 8750, UL924 CSA C22.2 No. 137, CSA C22.2 No. 250.0 CSA C22.2 No. 141, C22.2 No. 94.1, C22.2 No.94.2	-40°C to +40°C (-40°F to +104°F)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-6-B-C-P-ND Glass Lens	60W	Sold Out	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-6-A-C-P-D Glass Lens	60W	Sold Out Dimmable	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-6L-A-C-P-ND Glass Lens 6L (60W) = 12.5x9.45x6.5in	60W	110pcs	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-6L-B-I-P-D Glass Lens 6L (60W) = 12.5x9.45x6.5in	60W	67pcs ETA to WH 3/10 4000K	8100lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-6L-B-C-P-D Glass Lens 6L (60W) = 12.5x9.45x6.5in	60W	30pcs 200-480V	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-8-A-I-P-ND Glass Lens	80W	Sold Out 4000K	8100lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
















TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Picture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-8-A-C-P-D Glass Lens	80W	110pcs Dimmable	10400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX G-10-A-C-P-D Glass Lens	100W	280pcs Dimmable	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX G-10-A-I-P-ND Glass Lens	100W	47pcs 4000K	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-10-B-C-P-D Glass Lens	100W	65pcs DIM 200-480V	13500 lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-15-A-C-P-ND Glass Lens	150W	Sold Out	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-15-A-C-P-D Glass Lens	150W	355pcs Dimmable	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-15-B-C-P-D Glass Lens	150W	Sold Out 200-480V	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-20-A-C-P-ND Glass Lens	200W	Sold Out	28000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-20-A-C-P-D Glass Lens	200W	100pcs 4000K	28000lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-20-A-C-P-D Glass Lens	200W	500pcs Dimmable	28000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-25-A-C-P-D Glass Lens	250W	47pcs Dimmable	35,000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX-G-30-A-C-P-D Glass Lens	300W	15pcs Dimmable	42000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Galaxy Series Flood Light Class I, Division II		FME-GAX G-40-A-C-P-D Glass Lens	400W	100pcs Dimmable	56000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-4-A-I-ND-5Y	40W	3pcs 50pcs ETA 3/10 4000K	8100 lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-MOO-6-A-C-P-ND-5Y	60W	Sold Out	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3	-104°F to 122°F (- 40°C to +50°C)
















TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Picture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Moon Series Highbay Class I, Division II		FME-M00-6-A-C-P-D-5Y	60W	Sold Out Dimmable	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-M00-6L-A-C-P-D-5Y	60W	Sold Out Dimmable	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-M00-8-A-C-P-ND-5Y	80W	Sold Out	10800lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-M00-8-A-I-P-D-5Y	80W	20pcs Dimmable 4000K	10800lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-M00-8-A-C-P-D-5Y	80W	500pcs Dimmable	10800lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 122°F (- 40°C to +50°C)
Moon Series Highbay Class I, Division II		FME-M00-10- A-C-P-ND-5Y	100W	Sold Out	14000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-M00-10- A-C-P-D-5Y	100W	210pcs Dimmable	14000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-M00-15-A-C-P-ND-5Y	150W	Sold Out	21000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-M00-15-A-I-P-D-5Y	150W	30pcs Dimmable 4000K	21000lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-M00-15-A-C-P-D-5Y	150W	185pcs Dimmable	21000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-M00-15-B-C-P-D-5Y	150W	20pcs Dimmable 200-480V	21000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-M00-20-B-C-P-ND-5Y	200W	Sold Out	28000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-M00-20-A-I-P-ND-5Y	200W	Sold Out 4000K	28000lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-M00-20-A-C-P-D-5Y	200W	35pcs 105pcs ETA to WH 3/15 Dimmable	28000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-M00-20-B-C-P-D-5Y	200W	45pcs Dimmable 200-480V	28000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G ClassIII Temp. Code: T3 Other: IP66 IK10	-104°F to 104°F (- 40°C to +40°C)



TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Picture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Moon Series Highbay Class I, Division II		FME-MOO-25-A-C-P-D-5	250W	15pcs ETA to WH 4/15 Dimmable	33750lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3Other: IP66 IK10	-104°F to 104°F (-40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-30-A-C-P-D-5Y	300W	80pcs Dimmable	42000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3Other: IP66 IK10	-104°F to 104°F (-40°C to +40°C)
Moon Series Highbay Class I, Division II		FME-MOO-40-A-C-P-D-5Y	400W	3pcs Dimmable	56000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3Other: IP66 IK10	-104°F to 104°F (-40°C to +40°C)
Star Series Highbay Class I, Division I		FME-STA-4-42-A-C-R-D-5Y	40W	30pcs Dimmable	5400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK1	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-6-42-A-I-R-ND-5Y	60W	55pcs 4000K	8400lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK1	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-6-42-A-C-R-D-5Y	60W	205pcs Dimmable	8400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK1	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-8-42-A-I-R-ND-5Y	80W	75pcs 4000K	11200lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK1	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-8-42-A-C-R-D-5Y	80W	230pcs Dimmable	11200lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK1	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-10-42-A-C-R-ND-5Y	100W	Sold Out	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-10-42-A-I-R-ND-5Y	100W	100pcs 4000K	13500lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-10-42-A-C-R-D-5Y	100W	370pcs Dimmable	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-15-42-B-I-R-D-5Y	150W	Sold Out Dimmable 200-480V	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-15-42-A-C-R-D-5Y	150W	255pcs Dimmable	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-15-42-A-I-R-ND-5Y	150W	53pcs 4000K	20250lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-20-42-A-I-R-ND-5Y	200W	40pcs 4000K	27000 lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
















TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Picture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Star Series Highbay Class I, Division I		FME-STA-20-42-A-I-R-D-5Y	200W	50pcs Dimmable	27000 lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-20-42-B-C-R-D-5Y	200W	Sold Out Dimmable 200-480V	27000 lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-10-42-A-C-R-D-5Y-OPGG <i>with Frosted Globe & Guard</i>	100W	20pcs Dimmable	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-24-42-A-C-R-D-5Y	240W	Sold Out Dimmable	32400 lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Star Series Highbay Class I, Division I		FME-STA-25-42-A-C-R-D-5Y	250W	130pcs Dimmable	35000lm	5000K	120°	Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)
Earth Series Flood Light/High Bay Class I, Division I		FME-EAT-G-6-A-C-P-ND-5Y <i>Glass Lens</i>	60W	150pcs	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	104°F to 131°F (-40°C to +55°C)
Earth Series Flood Light/High Bay Class I, Division I		FME-EAT-G-6-A-I-P-ND-5Y <i>Glass Lens</i>	80W	15pcs 4000K	8100lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	104°F to 131°F (-40°C to +55°C)
Earth Series Flood Light/High Bay Class I, Division I		FME-EAT-G-8-A-C-P-D-5Y <i>Glass Lens</i>	80W	140pcs Dimmable	11200lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 131°F (-40°C to +55°C)
Earth Series Flood Light/High Bay Class I, Division I		FME-EAT-G-10-A-C-P-ND-5Y <i>Glass Lens</i>	100W	2pcs	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 131°F (-40°C to +55°C)
Earth Series Flood Light/High Bay Class I, Division I		FME-EAT-G-10-A-C-P-D-5 <i>Glass Lens</i>	100W	123pcs Dimmable	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 131°F (-40°C to +55°C)
Earth Series Flood Light/High Bay Class I, Division I		FME-EAT-G-10-A-I-P-ND-5 <i>Glass Lens</i>	150W	30pcs ETA to WH 4/15 4000K	20250lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 131°F (-40°C to +55°C)
Earth Series Flood Light/High Bay Class I, Division I		FME-EAT-G-15-A-C-P-D-5Y <i>Glass Lens</i>	150W	106pcs Dimmable	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 131°F (-40°C to +55°C)
Earth Series Flood Light/High Bay Class I, Division I		FME-EAT-G-15-B-C-P-ND-5Y <i>Glass Lens</i>	150W	15pcs 50pcs ETA to WH 4/15 200-480V	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 131°F (-40°C to +55°C)
MRT Series Maritron Flanged Ceiling Surface Mount, Class I, Division II		MRT-B-4-LV1-C-D-CM <i>Includes 1 Meter Chains and Lift rings</i>	40W	28pcs Dimmable	5200lm 1X4	5000K	120°	Marine: UL 1598, UL 844, UL 924 UL 844: Class I, Division II, Group A,B,C, D Temp. Code: T4 Other: IP66 IK10	-40°C to 60°C
MRT Series Maritron Flanged Ceiling Surface Mount, Class I, Division II		MRT-C-4-LV1-C-D-CM <i>Includes 1 Meter Chains and Lift rings</i>	40W	43pcs Dimmable	5200lm 2X2	5000K	120°	Marine: UL 1598, UL 844, UL 924 UL 844: Class I, Division II, Group A,B,C, D Temp. Code: T4 Other: IP66 IK10	-40°C to 60°C
















TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Picture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
MRT Series Maritron Flanged Ceiling Surface Mount, Class I, Division II		MRT-D-6-LV1-C-D-CM <i>Includes 1 Meter Chains and Lift rings</i>	60W	20pcs Dimmable	7800lm 2X4	5000K	120°	Marine:UL 1598,UL844,UL924 UL 844: Class I,DivisionII, GroupA,B,C, D Temp.Code:T4 Other:IP66 IK10	-40°C to 60°C
Mercury Series Highbay Class I, Division I		FME-MER-10-A-I-R-ND-5Y	100W	42pcs	13500lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Mercury Series Highbay Class I, Division I		FME-MER-15-A-I-R-ND-5Y	150W	8pcs	20250lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Mars Series Jelly Jar Class I, Division I		FME-MAR-2-A-C-ND-5Y-CGG <i>Clear Globe w/ Wire Guard</i>	20W	10pcs	2700lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Mars Series Jelly Jar Class I, Division I		FME-MAR-3-A-C-P-ND-5Y-CGG <i>Clear Globe w/ Wire Guard</i>	30W	Sold Out	4050 lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Mars Series Jelly Jar Class I, Division I		FME-MAR-3-A-C-P-D-5Y-CGG <i>Clear Globe w/ Wire Guard</i>	30W	115pcs 100pcs ETA to WH 4/15 Dimmable	3900lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Mars Series Jelly Jar Class I, Division I		FME-MAR-4-A-I-P-ND-5Y-CGG <i>Clear Globe w/ Wire Guard</i>	40W	90pcs 4000K	3900lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Mars Series Jelly Jar Class I, Division I		FME-MAR-4-A-C-P-D-5Y-CGG <i>Clear Globe w/ Wire Guard</i>	40W	180pcs ETA to WH 3/12 Dimmable	3900lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II,Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Universe Series Jelly Jar Class I, Division II		FME-UNI-2-A-C-ND-5Y-OPCM-CGG <i>Ceiling Surface Mount Clear Globe with Wire Guard</i>	20W	176pcs	2800lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I,Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Universe Series Jelly Jar Class I, Division II		FME-UNI-3-A-C-ND-5Y-OPCM-CGG <i>Ceiling Surface Mount Clear Globe with Wire Guard</i>	30W (27W)	20pcs	4200lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I,Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Universe Series Jelly Jar Class I, Division II		FME-UNI-2-A-C-ND-5Y-P-CGG <i>Pedant Mount Clear Globe with Wire Guard</i>	20W	135pcs	2800lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I,Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK11	-104°F to 140°F (- 40°C to +60°C)
Universe Series Jelly Jar Class I, Division II		FME-UNI-3-A-C-ND-5Y-P-CGG <i>Pedant Mount Clear Globe with Wire Guard</i> 30W is being updated to 27W	30W (27W)	Sold Out	4200lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I,Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK11	-104°F to 140°F (- 40°C to +60°C)
Universe Series Jelly Jar Class I, Division II		FME-UNI-2-A-C-ND-5Y-OPWA-CGG <i>90 Degree Wall Mount Clear Globe with Wire Guard</i>	20W	70pcs	2800lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Universe Series Jelly Jar Class I, Division II		FME-UNI-3-A-C-ND-5Y-OPWA-CGG <i>90 Degree Wall Mount Clear Globe with Wire Guard</i> 30W is being updated to 27W	30W (27W)	90pcs 50pcs ETA to WH 4/15	4200lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-2-2-LV-I-P-ND-5Y	20W	20pcs 4000K	5400lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10	-104°F to 140°F (-40°C to +60°C)













TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Picture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Pluto Series Linear Class I, Division II		FME-PLU-2-2-LV-C-P-ND-5Y	20W	15pcs	5400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-2-4-LV-C-P-ND-5Y	40W	Sold Out	5400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-4-4-LV-C-P-D-5Y	40W	290pcs Dimmable	5400 lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-4-4-LV-I-ND-5Y	40W	25pcs 4000K	8100lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-4-6-LV-I-P-ND-5Y	60W	85pcs 4000K	8100lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-4-6-LV-C-P-D-5Y	60W	57pcs 100pcs ETA to BG 4/15 Dimmable	8100lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Pluto Series Linear Class I, Division II		FME-PLU-4-8-LV-C-P-D-5Y	80W	58pcs Dimmable	10800lm	5000K	120°	Marine: UL 1598A, UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G, IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-2-G-4-A-I-R-ND-5Y Glass Lens	40W	47pcs 4000K	5400lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D	-104°F to 140°F (-40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-2-G-4-A-C-R-ND-5Y Glass Lens	40W	24pcs	5400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D	-104°F to 140°F (-40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-2-G-5-A-C-R-D-5Y Glass Lens	50W	210pcs Dimmable	7000lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D	-104°F to 140°F (-40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-4-A-C-R-ND-5Y Glass Lens	40W	Sold Out	5400lm	5000K	120°	Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-4-A-C-R-D-5Y Glass Lens	40W	120pcs Dimmable	5400lm	5000K	120°	Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-6-A-I-R-D-5Y Glass Lens	60W	120pcs 4000K	8100lm	4000K	120°	Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-6-A-C-R-D-5Y Glass Lens	60W	215pcs Dimmable	8100lm	5000K	120°	Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (-40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-8-A-C-R-ND-5Y Glass Lens	80W	Sold Out	10800lm	5000K	120°	Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (-40°C to +60°C)

TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Picture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
Sun Series Linear Class I, Division I		FME-SUN-4-G-8-A-I-R-ND-5Y Glass Lens	80W	90pcs 4000K	10800lm	4000K	120°	Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-8-A-C-R-D-5Y Glass Lens	80W	40pcs Dimmable	10800lm	5000K	120°	Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (- 40°C to +60°C)
Sun Series Linear Class I, Division I		FME-SUN-4-G-10-A-C-R-D-5Y Glass Lens	100W	70pcs Dimmable	13500lm	5000K	120°	Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10 Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 104°F
Meridian Series Vaportight Class I, Division II		FME-MID-24-3-A-C-P-D-SM-5Y 2FT	30W	230pcs Dimmable	4050lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 113°F (- 40°C to +45°C)
Meridian Series Vaportight Class I, Division II		FME-MID-24-3-A-I-P-D-SM-5Y 2FT	30W	5pcs 4000K	4050lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 113°F (- 40°C to +45°C)
Meridian Series Vaportight Class I, Division II		FME-MID-24-4-A-C-P-D-SM-5Y 2FT	40W	43pcs 100pcs ETA to WH 3/15 Dimmable	5400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 113°F (- 40°C to +45°C)
Meridian Series Vaportight Class I, Division II		FME-MID-48-5-A-I-P-ND-SM-5Y 4FT	50W	150pcs 4000K	6750lm	4000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 113°F (- 40°C to +45°C)
Meridian Series Vaportight Class I, Division II		FME-MID-48-5-A-C-P-D-SM-5Y 4FT	50W	150pcs Dimmable	6750lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 113°F (- 40°C to +45°C)
Meridian Series Vaportight Class I, Division II		FME-MID-48-6-A-C-P-D-SM-5Y 4FT	60W	360pcs Dimmable	6750lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-104°F to 113°F (- 40°C to +45°C)
Meridian-R Series Hazardous location & NSF Rated Class I, Division II		MID-R-24-3-1-C-P-D 2FT 304 Stainless steel White NSF	30W	87pcs Dimmable	4050lm	5000K	120°	NSF-Rated Optional Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-40°C to +40°C (T6) -40°C to +60°C (T5)
Meridian-R Series Hazardous location & NSF Rated Class I, Division II		MID-R-48-5-A-C-P-D 4FT 304 Stainless steel White NSF	50W	60pcs Dimmable	6750lm	5000K	120°	NSF-Rated Optional Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	-40°C to +40°C (T6) -40°C to +60°C (T5)
XF Linear Light Class I, Division II		XF-2-4-C-D-Z-WM 2FT	40W	55pcs Dimmable	5600lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T5/T4 Other: IP66 IK10	T5(-40°C to +40°C) T4(-40°C to +55°C)
XF Linear Light Class I, Division II		XF-4-6-C-D-Z-WM 4FT	60W	60pcs 100pcs ETA to WH 4/15 Dimmable	8400lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T5/T4 Other: IP66 IK10	T5(-40°C to +40°C) T4(-40°C to +55°C)
XF Linear Light Class I, Division II		XF-4-8-C-D-Z-WM 4FT	80W	176pcs Dimmable	10800lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T5/T4 Other: IP66 IK10	T5(-40°C to +40°C) T4(-40°C to +55°C)
LFL Series, Flood/Area Light Class I, Division II		LFL-1-E-LV1-C-Z-TM	200W	190pcs	2600lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III	- 104°F to 131°F (-40°C to +55°C)

TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Series	Picture	Model	Wattage	Stock Available	Lumens	CCT	Beam Angle	Ratings	Ambient Operation Temperature
LFL Series, Flood/Area Light Class I, Division II		LFL-2-D-LV1-C-Z-TM	150W	45pcs	19500lm	5000K	120°	Temp.Code: T4(LFL2),T3(LFL1) Other:IP66 IK10	-104°F to 131°F (-40°C to +55°C)
LFL Series, Flood/Area Light Class I, Division II		LFL-2-C-LV1-C-Z-TM	100W	66pcs	13500lm	5000K	120°	Temp.Code: T4(LFL2),T3(LFL1) Other:IP66 IK10	-104°F to 131°F (-40°C to +55°C)
ZTP Series Exit Light Class I, Division I		ZTP-5-RD-LV <i>Double-Faced with Red letters & White Panel</i>	5W	220pcs	650lm	5000K	120°	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	-104°F to 140°F (-40°C to +60°C)
LUMIX-G Series (LGE) Exit Light Class I, Division II		LGE-5-LV-G-WM <i>Green Leds</i>	5W	18pcs	300lm	5000K	120°	Marine:UL 1598A,ABS UL 844: Class I, DivisionII, GroupA,B,C,D ClassII, DivisionI & II, Group E,F,G ClassIII Temp.Code: T5/T4 Other:IP66 IK10	Ta= 0°C to + 45°C, when battery is charged; Ta= -10°C to + 60°C, when battery discharges
XPESC Combo Class I, Division II		EPESC-A-GN-12V-15-GR-SDT <i>SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.</i>	15W	60pcs	/	Green	120°	Meets UL924, UL844, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes. UL 844: Class I DivisionII, GroupA,B,C, D IP66	0°C – 50°C on 12W / 15W and 10°C- 40°C models. Up TO (-20°C – 50°C). WITH CW OPTION
XPESC Combo Class I, Division II		EPESC-A-RD-6V-15-GR	15W	28pcs	/	Red	120°	Meets UL924, UL844, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes. UL 844: Class I DivisionII, GroupA,B,C, D IP66	0°C – 50°C on 12W / 15W and 10°C- 40°C models. Up TO (-20°C – 50°C). WITH CW OPTION
CRUZ SERIES EXIT Class I, Division II		CRU-1-RD-GY-EM	3W	84pcs	/	Red	120°	Meets UL924, UL844, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes. UL 844: Class I, DivisionII, GroupA,B,C,D IP66	0°C – 50°C on 12W / 15W and 10°C - 40°C models. Up TO (-20°C – 50°C). WITH CW OPTION
CRUZ SERIES EXIT Class I, Division II		CRU-1-RD-GY-EM-SDT <i>SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.</i>	3W	115pcs	/	Red	120°	Meets UL924, UL844, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes. UL 844: Class I, DivisionII, GroupA,B,C,D IP66	0°C – 50°C on 12W / 15W and 10°C - 40°C models. Up TO (-20°C – 51°C). WITH CW OPTION
HEL SERIES EMERGENCY Class I, Division II		HEL-12-15-G	15W	47pcs	/	/	120°	Meets UL924, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes. UL 844: Class I, DivisionII, GroupA,B,C, D IP66	0°C – 50°C). Up TO (-20°C – 50°C). WITH CW OPTION
HEL SERIES EMERGENCY Class I, Division II		HEL-12-15-G-SDT <i>SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.</i>	15W	60pcs	/	/	120°	Meets UL924, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes. UL 844: Class I, DivisionII, GroupA,B,C, D IP66	0°C – 50°C). Up TO (-20°C – 50°C). WITH CW OPTION

TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

STOCK ONLY Hazardous Location/Explosion Proof - USA Inventory














FME LIGHTING | 877-234-8460 | info@fmelighting.com

PRICING Q4 2024 FIRM UNTIL 4-29-25

Inventory Levels as of Feb 28, 2025






Accessories 13 to 23 are compatible with all series with the exception of the LIH, NEB, SOL & ROC

ACCESSORIES

Picture	Model	Stock Available	Description
	SOL-CM	21pcs	Ceiling Mount Bracket for Solstice Series 4x 3/4"NPT Cable Entries, 3 sealed by blanking plugs
	SOL-WM	43pcs	Wall Mount Bracket for Solstice Series 4x 3/4"NPT Cable Entries, 3 sealed by blanking plugs
	NEB-CM	25pcs	Ceiling Mount Bracket for Nebula Series 4x 3/4"NPT Cable Entries, 3 sealed by blanking plugs
	NEB-WM	52pcs	Wall Mount Bracket for Nebula Series 4x 3/4"NPT Cable Entries, 3 sealed by blanking plugs
	ROC-PLM	50pcs	Rocket Series Pole Adaptor
	1- Meter Safety Chain	5pcs	1- Meter Safety Chain
	Slip Fitter	190pcs	Slip Fitter
	OPEB	250pcs	JUNCTION BOX C1,D1
	FME-MID-PM	90sets	Mounting Pole & Clamp for Meridian (MID) Series fixtures
	OPWA25	128pcs	C1, D1 25 DEGREE WALL MOUNT
	OPPS90	170pcs	C1, D1 90 DEGREE WALL MOUNT & JUNCTION Box

TERMS:

1) Shipments are from California. Quantities subject to change on daily basis.

Picture	Model	Stock Available	Description
	OPPS25	310pcs	25 DEGREE POLE MOUNT
	OPPS90	185pcs	90 DEGREE POLE MOUNT
	OPWA	215pcs	90 DEGREE WALL MOUNT
	NIP-3/4	500pcs	3/4" THREADED CONDUIT NIPPLE
	HOOK-1	113pcs	3/4" HOOK