


LED Explosion Proof - USA Inventory

Marine • Petrochemical • Oil & Gas • Food & Beverage • Waste Management • Aerospace • Steel • Pulp & Paper • Coal & Dust Storage • Power Generation • LNG • Mining



Model	Wattage	STOCK AVAILABLE 1.23.2023	Lumens	CCT	Beam Angle	Ambient Operation Temperature	Ratings	Fixture Size (inch)
-------	---------	------------------------------	--------	-----	---------------	----------------------------------	---------	------------------------

ZTL Series Exit Light Class I, Division I

								
	5W	23pcs	650lm	5000K	120°	-104°F to 140°F (-40°C to +60°C)	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	16.42'x16.74'x4.5 7'




Model	Wattage	STOCK AVAILABLE 1.23.2023	Lumens	CCT	Beam Angle	Ambient Operation Temperature	Ratings	Fixture Size (inch)
-------	---------	------------------------------	--------	-----	---------------	----------------------------------	---------	------------------------

Universe Series Jelly Jar Class I, Division II

								
	20W	75pcs	2800lm	5000K	120°	-104°F to 140°F (-40°C to +60°C)	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	5.4x5.4x11
	20W	100pcs	2800lm	5000K	120°	-104°F to 140°F (-40°C to +60°C)	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	5.4x5.4x11
	30W	98pcs	4200lm	5000K	120°	-104°F to 140°F (-40°C to +60°C)		5.4x5.4x11
	40W	90pcs	5400lm	5000K	120°	-104°F to 140°F (-40°C to +60°C)		5.4x5.4x11


Model	Wattage	STOCK AVAILABLE 1.23.2023	Lumens	CCT	Beam Angle	Ambient Operation Temperature	Ratings	Fixture Size (inch)
-------	---------	------------------------------	--------	-----	---------------	----------------------------------	---------	------------------------

Galaxy Series Flood Light Class I, Division II

		60W	Sold out	8100lm	5000K	120°	-104°F to 122°F (-40°C to +40°C)	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	10.2x6.3x8.1
	Dimmable	60W	261pcs	8100lm	5000K	120°			
		60W	Sold out	8100lm	5000K	120°	-104°F to 122°F (-40°C to +40°C)	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	12.5x9.45x6.5
		80W	Sold out	10400lm	5000K	120°			
	Dimmable	80W	53pcs	10400lm	5000K	120°			
		150W	Sold out	20250lm	5000K	120°	-104°F to 122°F (-40°C to +40°C)	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	14.9x9.1x7.4
	Dimmable	150W	238pcs	20250lm	5000K	120°			
		200-480V	5pcs	20250lm	5000K	120°			
		200W	Sold out	28000lm	5000K	120°			
	Dimmable	200W	290pcs	28000lm	5000K	120°			


LED Explosion Proof - USA Inventory




	Dimmable	250W	95pcs	33750lm	5000K	120°	-104°F to 122°F (-40°C to +40°C)	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	16.7x11.8x8.3
	Dimmable	300W	49pcs	42000lm	5000K	120°			
	Dimmable	400W	83pcs	56000lm	5000K	120°			


Model	Wattage	STOCK AVAILABLE 1.23.2023	Lumens	CCT	Beam Angle	Ambient Operation Temperature	Ratings	Fixture Size (inch)
-------	---------	------------------------------	--------	-----	------------	-------------------------------	---------	---------------------

Moon Series Highbay Class I, Division II

		60W	Sold out	8100lm	5000K	120°	-104°F to 122°F (-40°C to +50°C)	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3	9.06x9.06x8.99
	Dimmable	60W	280pcs	8100lm	5000K	120°			

		60W	120pcs	8100lm	5000K	120°	-104°F to 122°F (-40°C to +50°C)	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	10.6x10.6x10.5
		80W	Sold out	10800lm	5000K	120°			
	Dimmable	80W	300pcs	10800lm	5000K	120°			

		100W	Sold out	14000lm	5000K	120°	-104°F to 104°F (-40°C to +40°C)	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	14.6x14.6x7.8	
	Dimmable	100W	273pcs	14000lm	5000K	120°				
		150W	Sold out	21000lm	5000K	120°				
	Dimmable	150W	300pcs	21000lm	5000K	120°				
	Dimmable	200-480V	15W	15pcs	21000lm	5000K				120°
		200W	Sold out	28000lm	5000K	120°				
	Dimmable	200W	128pcs	28000lm	5000K	120°				

	Dimmable	250W	97pcs	33750lm	5000K	120°	-104°F to 104°F (-40°C to +40°C)	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	18.9x18.9x15.5
	Dimmable	300W	70pcs	42000lm	5000K	120°			
	Dimmable	400W	95pcs	56000lm	5000K	120°			



Model	Wattage	STOCK AVAILABLE 1.23.2023	Lumens	CCT	Beam Angle	Ambient Operation Temperature	Ratings	Fixture Size (inch)
-------	---------	------------------------------	--------	-----	------------	-------------------------------	---------	---------------------

Star Series Highbay Class I, Division I

	Dimmable	40W	50pcs	5400lm	5000K	120°	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	14x14x9.3
	Dimmable	60W	110pcs	8400lm	5000K	120°			
		80W	Sold out	11200lm	5000K	120°			
	Dimmable	80W	260pcs	11200lm	5000K	120°			



LED Explosion Proof - USA Inventory



		100W	Sold out	13500lm	5000K	120°	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	16x16x10.5
	Dimmable	100W	221pcs	13500lm	5000K	120°			
		150W	Sold out	20250lm	5000K	120°			
	Dimmable 200-480V	150W	Sold out	20250lm	5000K	120°			
	Dimmable	150W	170pcs	20250lm	5000K	120°			
	Dimmable	240W	Sold out	32400lm	5000K	120°	277VAC, -40°C to 55°C (-104°F to 131°F) 120VAC, -40°C to 40°C (-104°F to 104°F)	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	17.44x17.44x10
	Dimmable	250W	39pcs	35000lm	5000K	120°			


Model Wattage **STOCK AVAILABLE 1.23.2023** Lumens CCT Beam Angle Ambient Operation Temperature Ratings Fixture Size (inch)

Earth Series Flood Light Class I, Division I

	100-277V	60W	30pcs	8100lm	5000K	120°	-104°F to 131°F (-40°C to +55°C)	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	11.6x11.6x9.57
	Dimmable	80W	106pcs	11200lm	5000K	120°			11.6x11.6x9.57
	100-277V	100W	28pcs	13500lm	5000K	120°	-104°F to 131°F (-40°C to +55°C)	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	15.7x11.2x7.6
	100-277V Dimmable	100W	145pcs	13500lm	5000K	120°			
	100-277V Dimmable	150W	180pcs	20250lm	5000K	120°			
	200-480V	150W	38pcs	20250lm	5000K	120°			


Model Wattage **STOCK AVAILABLE 1.23.2023** Lumens CCT Beam Angle Ambient Operation Temperature Ratings Fixture Size (inch)

Mercury Series Highbay Class I, Division I

		100W	40pcs	13500lm	5000K	120°	-104°F to 140°F (-40°C to +60°C)	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	14.2x14.2x10.8
		150W	27pcs	20250lm					

Model Wattage **STOCK AVAILABLE 1.23.2023** Lumens Beam Angle Ambient Operation Temperature Ratings Fixture Size (inch)

Mars Series Jelly Jar Class I, Division I

		30W	Sold out	4050lm	5000K	120°	-104°F to 140°F (-40°C to +60°C)	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	6.8x6.8x16.1
	Dimmable	30W	300pcs	3900lm	5000K	120°			
	Dimmable	40W	320pcs	3900lm	5000K	120°			

LED Explosion Proof - USA Inventory



	Model	Wattage	STOCK AVAILABLE 1.23.2023	Lumens	CCT	Beam Angle	Ambient Operation Temperature	Ratings	Fixture Size (inch)
Pluto Series Linear Class I, Division II									
2FT		40W	125pcs	5400lm	5000K	120°	-104°F to 140°F (-40°C to +60°C)		2ft 23.62x4.7x8.85
4FT		40W	102pcs	5400 lm	5000K	120°	-104°F to 140°F (-40°C to +60°C)	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	4ft 47x4.7x9.5
		60W	Sold out	8100lm	5000K	120°			
		Dimmable 60W	350pcs	8100lm	5000K	120°			
		Dimmable 80W	130pcs	10800lm	5000K	120°			
Sun Series Linear Class I, Division I									
2FT		50W	Sold out	7000lm	5000K	120°	-104°F to 140°F (-40°C to +60°C)	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	2ft 23.23x4.7x8.13
		Dimmable 50W	110pcs	7000lm	5000K	120°			
4FT		40W	Sold out	5400lm	5000K	120°	-104°F to 140°F (-40°C to +60°C)	Marine: UL 1598A, ABS UL 844: Class I, Division I, Group C,D Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T4 Other: IP66 IK10	4ft 47x4.7x98.13
		Dimmable 40W	136pcs	5400lm	5000K	120°			
		60W	Sold out	8100lm	5000K	120°			
		Dimmable 60W	200pcs	8100lm	5000K	120°			
		80W	15pcs	10800lm	5000K	120°			
		Dimmable 80W	290pcs	10800lm	5000K	120°			
		Dimmable 100W	125pcs	13500lm	5000K	120°	-104°F to 104°F (-40°C to +40°C)		
Meridian Series Vaportight Class I, Division II									
2FT		Dimmable 30W	134pcs	4050lm	5000K	120°	-104°F to 113°F (-40°C to +45°C)	Marine: UL 1598A, ABS UL 844: Class I, Division II, Group A,B,C,D Class II, Division I & II, Group E,F,G Class III Temp. Code: T3 Other: IP66 IK10	2ft 27.5x8.7x4.8
		Dimmable 40W	94pcs	5400lm	5000K	120°			
4FT		Dimmable 50W	135pcs	6750lm	5000K	120°			4ft 52x8.7x5.5